

Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Covering varnish BLUE JE703

Further trade names

Paints and varnishes

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Metal surface treatment products

1.3. Details of the supplier of the safety data sheet

Company name:	Jentner Plating Technology GmbH	
Street:	Johann-Staib-Strasse 2	
Place:	D-75179 Pforzheim	
Telephone:	+49 (0)7231 418094 0	Telefax: +49 (0)7231 418094 77
e-mail:	info@jentner.de	
Contact person:	Department of Chemistry	
Internet:	www.jentner.de	
Responsible Department:	Poison Information Center of the University of Freiburg.	

1.4. Emergency telephone number:

0049 (0)761 19240 - 24 h german and english

Further Information

BfR Produktnummer: 6265770

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:


Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Warning**Pictograms:****Hazard statements**

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 2 of 9

P501 Return contents/container to the point of sale or to a special waste collection point.

Special labelling of certain mixturesEUH066 Repeated exposure may cause skin dryness or cracking.
Restricted to professional users.**2.3. Other hazards**

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**Mixture of subsequent listed substances with not dangerous additives.
Solvent naphtha without benzol.**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-94-5	Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified			25-50 %
	265-198-5	649-424-00-3		
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Further Information

The classification is corresponding to the current EG-List, but it is supplemented by information from technical literature and companies detail.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**Self-protection of the first aider
Remove affected person from the danger area and lay down.
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).**After inhalation**In case of troubles or persistent symptoms, consult an ophthalmologist.
Provide fresh air.**After contact with skin**Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. After contact with skin, wash immediately with plenty of water and soap.
If skin irritation or rash occurs: Get medical advice/attention.**After contact with eyes**

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

Induce vomiting when the affected person is not unconscious. Rinse mouth immediately and drink plenty of water. Medical treatment necessary.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 3 of 9

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings. Carbon dioxide (CO₂), Water spray. Larger fires with alcohol resistant foam or water spray to combat.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Vapours can form explosive mixtures with air. Carbon monoxide
Nitrogen oxides (NO_x).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133). Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not empty into drains; dispose of this material and its container in a safe way.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Do not allow to enter into surface water or drains.

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations. General Precautions for safe handling of chemicals.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Keep away from heat. Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 4 of 9

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Keep locked up and out of the reach of children.

Hints on joint storage

Do not store together with: Food and feedingstuffs

7.3. Specific end use(s)

Metal surface treatment products

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. See chapter 7. Additional information on plant design:

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. General Precautions for safe handling of chemicals.

Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Wear suitable gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Do not breathe gas/fumes/vapour/spray.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	viscous
Colour:	blue
Odour:	characteristic

Test method

Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 5 of 9

Changes in the physical state

Flash point: >60 °C

Flammability

Solid: not applicable

Gas: not applicable

Explosive properties

No data available

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 7,0 vol. %

Ignition temperature: 450 °C DIN 51794

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

oxidising

Vapour pressure: < 1 hPa

Density (at 20 °C): 1,07 g/cm³

Water solubility: 0 g/L

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: 16000 mPa·s

Vapour density: not determined

Evaporation rate: not determined

Solvent separation test: <3%

Solvent content: ca. 44%

9.2. Other information

Solid content: 56%

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No decomposition if used as directed.

10.5. Incompatible materials

acid. Alkalis (alkalis), concentrated. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 6 of 9

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

LD50: > 6800 mg/kg rat oral.

LD50: > 3400 mg/kg rab dermal.

LC50: > 10,2 mg/l rat inhalative

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Toxic to fish.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080121 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint or varnish remover; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the

Covering varnish BLUE JE703


Revision date: 13.10.2020

Product code: 126

Page 7 of 9

same way as the substance itself. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), light aroma)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
	
Classification code:	M6
Special Provisions:	274 335 601
Limited quantity:	5 L
Transport category:	3
Hazard No:	90
Tunnel restriction code:	E

Other applicable information (land transport)

Special provisions: 274 335 601

Transport category: 3

Inland waterways transport (ADN)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), light aroma)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Classification code:	M6
Special Provisions:	274 335 601
Limited quantity:	5 L

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT Solvent naphtha (petroleum), light aroma)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9



Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 8 of 9

Special Provisions: 274, 335
 Limited quantity: 5 L
 EmS: F-A, S-F

Other applicable information (marine transport)

E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (PAINT Solvent naphtha (petroleum), light aroma)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9



Special Provisions: A97 A158
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

: Y964
 E1
 00000000004: Y914
 Special provisions: A97 A158

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

**14.6. Special precautions for user**

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 5 % (53,5 g/l)
 2004/42/EC (VOC): 5 % (53,5 g/l)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Covering varnish BLUE JE703

Revision date: 13.10.2020

Product code: 126

Page 9 of 9

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)